

[2017 New Free Lead2pass Cisco 400-101 VCE And PDF Instant Download (121-140)]

2017 July Cisco Official New Released 400-101 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! Cisco New Released Exam 400-101 exam questions are now can be download from Lead2pass! All questions and answers are the latest! 100% exam pass guarantee! Get this IT exam certification in a short time! Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/400-101.html>

QUESTION 121 Refer to the exhibit. If the default-information originate always command is configured on R4, what route type is assigned to the default route in R1's route table? A. OB. E2C. O IAD. E1 Answer: C

QUESTION 122 Refer to the exhibit. The spokes of the DMVPN with the given configuration are having QoS issues. Which two actions can you take to resolve the problem? (Choose two.) A. Configure qos pre-classify on the tunnel interface. B. Configure an NHRP group on the tunnel interface and associate it to a QoS policy. C. Modify the configuration of the IPsec policy to accept QoS policies. D. Manually configure a QoS policy on the serial interface. E. Configure the bandwidth statement on the tunnel interface. F. Configure the bandwidth statement on the serial interface. Answer: AB

QUESTION 123 Which command can you enter to prevent a router from displaying Telnet connection messages on the terminal? A. service telnet-zeroidle B. ip telnet hidden hostname C. ip telnet hidden address D. no ip domain-lookup E. ip telnet quiet Answer: E

QUESTION 124 Which description of Infrastructure as a Service is true? A. a cloud service that delivers on-demand Internet connection between sites B. a cloud service that delivers on-demand intranet connection between sites C. a cloud service that delivers on-demand software services on a subscription basis D. a cloud service that delivers on-demand resources like networking and storage Answer: D

QUESTION 125 Which two statements about VSS are true? (Choose two.) A. It requires physical switches to be collocated. B. It is dependent on spanning-tree. C. It requires three IP addresses per ULAN. D. Each VSS has a single management IP address. E. It can eliminate the need for HSRP. Answer: DE

QUESTION 126 For which reason can two OSPF neighbor routers on the same LAN segment be stuck in the two-way state? A. The two routers have different MTUs on the interface. B. The two routers are configured with different priorities. C. The interface priority is set to zero on both routers. D. Both routers have the same OSPF router ID. Answer: C

QUESTION 127 Which option is an example of SaaS? A. Google Apps B. Amazon AWS C. Google App Engine D. Microsoft Azure Answer: A

QUESTION 128 How does an IPv6 host automatically generate a global address? A. It prepends its interface identifier to the network prefixes contained in Router Advertisement messages. B. It appends its interface identifier to the network prefixes contained in Router Advertisement messages. C. It appends its interface identifier to the network prefixes contained in Router Solicitation messages. D. It prepends its interface identifier to the network prefixes contained in Router Solicitation messages. Answer: B

QUESTION 129 Which statement about the feasible distance in EIGRP is true? A. It is the maximum metric that should feasibly be considered for installation in the RIB. B. It is the smallest metric toward the destination encountered ...time the destination went from Active to Passive state. C. It is the metric that is supplied by the best next hop toward the destination. D. It is the maximum metric possible based on the maximum hop count that is allowed. Answer: B

Explanation: FD is a record of the lowest known distance since the last transition from the Active to Passive state.

QUESTION 130 Refer to the exhibit. What tag will be applied to the 172.16.130.0/24 route? A. 10 B. 20 C. 30 D. 40 Answer: B

QUESTION 131 What is wrong with the configuration of this tunnel interface? A. ISATAP tunnels cannot use the EUI-64 address format. B. No tunnel destination has been specified. C. The tunnel source of an ISATAP tunnel must always point to a loopback interface. D. Router advertisements are disabled on this tunnel interface. Answer: D

QUESTION 132 Which option describes how a network administrator prevents possible routing for VLSM subnets that are missing from the routing table? A. Create a route for the subnet to the null interface, and then redistribute the static route into the routing process. B. Create a loopback interface with the correct subnet, and then redistribute the connected interface to the routing table. C. Create a loopback interface with the correct subnet, and the routing protocol automatically injects it into its routing process. D. Create a route for the subnet to the null interface, and the routing protocol automatically injects it into its routing process. Answer: A

QUESTION 133 What are two potential drawbacks of VPLS? (Choose two.) A. VPLS devices drop all VLAN-tagged packets. B. VPLS increases the risk of routing loops. C. VPLS is poorly suited for large, flat network implementations. D. When more devices are added to the VPLS, packet replication is significantly increased. E. VPLS requires manual configuration for loop prevention. Answer: CD

QUESTION 134 What command can you enter on a Cisco router so that it can both poll a time server and be polled by a time server? A. ntp server B. ntp broadcast client C. ntp broadcast destination D. ntp peer Answer: D

QUESTION 135 Which two options are examples of Northbound and/or Southbound protocol? (Choose two) A. OpenStack B. ISIS C. NETCONF D. JSON E. BGP-LS Answer: CE

QUESTION 136 What are two differences between IPv6 ISATAP tunneling and IPv6 6to4 tunneling? (Choose two) A. Only ISATAP tunneling transfers unicast IPv6 packets between sites. B.

Only 6to4 tunneling requires 2002:: /16 addresses.C. Only ISATAP tunneling can transfer IPv6 multicast packets.D. Only ISATAP tunneling transfers unicast IPv6 packets within a site.E. Only 6to4 tunneling transfers unicast IPv6 packets within a site.
Answer: BD QUESTION 137A host on an Ethernet segment has a different subnet mask than the default gateway. What can be done to allow it to communicate with devices outside of this subnet? A. Configure a static route for the host on the default gateway.B. Configure a static ARP entry on the default gateway for the host IP address.C. Enable gratuitous ARP on the host.D. Enable proxy ARP on the default gateway. Answer: D QUESTION 138Drag and Drop QuestionDrag and drop the NETCONF layers on the left onto their appropriate description on the left. Answer: QUESTION 139Drag and Drop Question Answer: QUESTION 140 Drag and Drop QuestionDrag and drop each extended ping IP header option from the left onto the corresponding description on the right. Answer: Lead2pass gives the latest, authoritative and complete 400-101 braindumps for 400-101 exam, because of that, all of our candidates pass 400-101 certification without any problem. The biggest feature is the regular update of 400-101 PDF and VCE, which keeps our candidates' knowledge up to date and ensures their 400-101 exam success. 400-101 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDQndBMUJTakdhaEE> 2017 Cisco 400-101 exam dumps (All 708 Q&As) from Lead2pass: <http://www.lead2pass.com/400-101.html> [100% Exam Pass Guaranteed]